

HYUNDAI

MATERIAL HANDLING

NO ONE DELIVERS MORE

2025
FULL PRODUCT LINE





THE POWER TO DO MORE

The Hyundai brand has come to stand as a symbol of reliability, quality, value, and innovation. After over 75 years, it has gained this reputation through an array of groundbreaking products. From giant, oceangoing container ships to automobiles to electronics to forklifts, you will find the Hyundai brand and its commitment to excellence at work around the globe.

That commitment begins by creating solutions designed to help individuals and businesses reach their full potential. For our business partners, that means helping them maximize efficiency, productivity, and profitability, while working to create a more sustainable, equitable world.

As you explore our latest material handling solutions you will discover a wide range of equipment incorporating the most advanced technology to make owning, operating, and maintaining equipment easier and more economical than ever before.

But our pursuit of excellence is never ending. We will continue to bring you the solutions you need to compete ever more successfully in an ever more competitive world.

HiMATE

Our exclusive Hi-Mate Management System is simply one of the industry's most advanced remote management system and is available for integration on virtually all Hyundai forklifts.

LI-ION

Our electric forklifts are compatible with the latest Li-ion batteries, cutting maintenance costs while increasing the performance of both the machine and your entire operation.

H₂ HYDROGEN FUEL CELL

Hyundai is bringing to the global market the latest in hydrogen fuel cell technology that will usher in an age of greater efficiency and sustainability in a world dealing with climate change.

OVER 70 DIFFERENT MODELS THAT ALL HAVE ONE THING IN COMMON

Delivering more. That quality is built into every machine that carries the Hyundai name. It is a result of a combination of innovative features and performance advantages you won't find on other forklifts, but you will find throughout our lineup of electric, LPG, and diesel models.

Hyundai is proud to offer a complete line of forklifts, reach trucks, order pickers, pallet jacks, tuggers, and stackers. Load capacities range from 2,200 to 55,000 lbs. and are designed for applications as varied as warehouses, lumber, precast concrete, food & beverage, logistics, retail — any business that needs things picked, stored, moved, lifted, lowered, or shipped.

While each type of Hyundai forklift is designed for different applications and environments, they all share certain qualities: high performance, simplified maintenance, low emissions, maximum operator comfort, enhanced safety features, energy efficiency, and advanced technology that together deliver the power to do more — for less.



ELECTRIC FORKLIFTS THAT DELIVER MORE

More versatility. More maneuverability. More dependability. Hyundai electric forklifts bring you all of that and more. Our lineup includes three- and four-wheel models, cushion and pneumatic tires, sit-down and stand-up configurations, reach trucks and order pickers. All in a capacity range from 3,000 to 10,000 lbs.

Throughout our line, you'll find advanced features, like our multifunction digital cluster that displays essential information in real time. Plus, Hyundai forklifts can accept Li-ion batteries to deliver outstanding performance and opportunity charging with minimal maintenance.

Your operation will profit from forklifts that deliver faster working speeds to move more pallets per hour, while your operators will be more productive with spacious cabs and ergonomic features like full suspension seats.

All of this makes Hyundai electric forklifts your best choice for a wide range of applications indoors and out, including warehousing, manufacturing, food & beverage, retail & e-commerce, home centers, and nurseries.



15/18/20 BCS-9



Stand Up Counter Balance Forklift
3,000 - 4,000 lbs. capacity · Cushion Tire

15/18/20 BT-9U



Three Wheel Forklift 36V/48V
3,000 - 4,000 lbs. capacity · Pneumatic Tire

25/30/32BC-9U



Four Wheel Forklift 36V/48V
5,000 - 6,500 lbs. capacity · Cushion Tire

16/20B-9



Four Wheel Forklift 48V
3,200 - 4,000 lbs. capacity · Pneumatic Tire

| | | 15BCS-9 | 18BCS-9 | 20BCS-9 | 15BT-9U | 18BT-9U | 20BT-9U | |
|--|-------------------------------------|---------|------------------|------------------|--------------------|--------------------|--------------------|--------------------|
| Identification | Load Capacity | lb | 3,000 | 3,500 | 4,000 | 3,000 | 3,500 | 4,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 8,514 | 8,922 | 9,283 | 6,874 | 7,511 | 7,809 |
| | Axle-loading, Loaded Front / Rear | lb | 9,792 / 1,719 | 10,740 / 1,686 | 11,587 / 1,686 | 8,842 / 1,032 | 9,748 / 1,263 | 10,572 / 1,237 |
| | Axle-loading, Unloaded Front / Rear | lb | 4,380 / 4,133 | 4,411 / 4,511 | 4,554 / 4,729 | 3,646 / 3,228 | 3,838 / 3,673 | 3,804 / 4,005 |
| Wheels, Chassis, Tire Type | | | Cushion | Cushion | Cushion | Superelastic | Superelastic | Superelastic |
| Dimensions | Overhead Guard Height | in | 87.9 | 87.9 | 87.9 | 83.1 | 83.1 | 83.1 |
| | Length to Face of Forks | in | 67.99 | 67.99 | 70.7 | 78.35 | 78.3 | 79.72 |
| | Overall Width | in | 42 | 42 | 42 | 42.3 | 43.5 | 43.5 |
| | Turning Radius | in | 55 | 55 | 57.75 | 60.6 | 64.2 | 65.4 |
| Right-angle Stacking Aisle Width 40" x 48" | | in | 120.3 | 120.3 | 123 | 127 | 131.3 | 132.4 |
| Right-angle Stacking Aisle Width 48" x 32" | | in | 125.1 | 125.1 | 127.8 | 132 | 136.2 | 137.4 |
| Performance | Travel Speed Loaded / Unloaded | mph | 7.5 / 7.5 | 7.5 / 7.5 | 7.5 / 7.5 | 9.9 / 9.9 | 9.9 / 9.9 | 9.9 / 9.9 |
| | Drive Motor Rating | hp | 7.8 x 2 | 7.8 x 2 | 7.8 x 2 | 9.8 x 2 | 9.8 x 2 | 9.8 x 2 |
| | Pump (Lift) Motor Rating | hp | 25.2 | 25.2 | 25.2 | 27.2 | 27.2 | 27.2 |
| | Battery Voltage | v | 36 | 36 | 36 | 36 / 48 | 36 / 48 | 36 / 48 |
| | Battery Compartment (L x W x H)* | in | 38.4 x 18 x 31.5 | 38.4 x 18 x 31.5 | 38.4 x 20.4 x 31.5 | 38.7 x 21.8 x 25.6 | 38.7 x 25.1 x 25.6 | 38.7 x 25.1 x 25.6 |
| Others | Type of Drive Control | | AC | AC | AC | AC | AC | AC |

* In this case the Length = the dimension from the left side of the rear counterweight to the right.
The Width = the dimension from the rear of the truck to the forks.

| | | 25BC-9U | 30BC-9U | 32BC-9U | 16B-9 | 20B-9 | |
|--|-------------------------------------|---------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Identification | Load Capacity | lb | 5,000 | 6,000 | 6,500 | 3,200 | 4,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 9,824 | 10,913 | 11,413 | 6,945 | 7,672 |
| | Axle-loading, Loaded Front / Rear | lb | 13,457 / 1,878 | 15,424 / 2,110 | 16,096 / 15,600 | 9,259 / 1,213 | 10,692 / 1,389 |
| | Axle-loading, Unloaded Front / Rear | lb | 3,975 / 5,847 | 4,284 / 6,636 | 4,213 / 7,198 | 3,494 / 3,450 | 3,637 / 4,034.5 |
| Wheels, Chassis, Tire Type | | | Cushion | Cushion | Cushion | Solid Pneumatic | Solid Pneumatic |
| Dimensions | Overhead Guard Height | in | 88 | 88 | 88 | 83.1 | 83.1 |
| | Length to Face of Forks | in | 85 | 89 | 90 | 80.1 | 83.8 |
| | Overall Width | in | 44 | 44 | 44 | 42.3 | 43.5 |
| | Turning Radius | in | 75 | 78 | 79 | 68.2 | 71.6 |
| Right-angle Stacking Aisle Width 40" x 48" | | in | 140 | 143 | 144 | 132 | 135.7 |
| Right-angle Stacking Aisle Width 48" x 32" | | in | 147 | 151 | 152 | 138 | 141.5 |
| Performance | Travel Speed Loaded / Unloaded | mph | 9.3 / 10.6 | 9.3 / 10.6 | 9.3 / 10.6 | 9.9 / 10.6 | 9.9 / 10.6 |
| | Drive Motor Rating | hp | 18.7 | 18.7 | 25.2 | 8.5 x 2 | 8.5 x 2 |
| | Pump (Lift) Motor Rating | hp | 22.8 | 22.8 | 30.5 | 25.2 | 25.2 |
| | Battery Voltage | v | 36 / 48 | 36 / 48 | 36 / 48 | 48 | 48 |
| | Battery Compartment (L x W x H)* | in | 39.2 x 30.8 x 23.8 | 39.2 x 34.8 x 23.8 | 39.2 x 34.5 x 23.8 | 38.7 x 21.7 x 25.6 | 38.7 x 25.1 x 25.6 |
| Others | Type of Drive Control | | AC | AC | AC | AC | AC |

* In this case the Length = the dimension from the left side of the rear counterweight to the right.
The Width = the dimension from the rear of the truck to the forks.

25/30/32/35B-X



Four Wheel Forklift 48V
5,000 - 7,000 lbs. capacity · Pneumatic Tire

25/30/32/35 B-9U



Four Wheel Forklift 36V/48V
5,000 - 7,000 lbs. capacity · Pneumatic Tire

25/30/35BH-9



Four Wheel Forklift 80V
5,000 - 7,000 lbs. capacity · Pneumatic Tire

40/45/50B-9



Four Wheel Forklift 80V
8,000 - 10,000 lbs. capacity · Pneumatic Tire

| | | | 25B-X | 30B-X | 32B-X | 35B-X | 25B-9U | 30B-9U | 32B-9U | 35B-9U |
|--|-------------------------------------|-----|-------------------------|-------------------------|-------------------------|-------------------------|--------------------|--------------------|--------------------|--------------------|
| Identification | Load Capacity | lb | 5,000 | 6,000 | 6,400 | 7,000 | 5,000 | 6,000 | 6,500 | 7,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 10,340 | 11,306 | 11,746 | 12,291 | 9,612 | 10,214 | 10,626 | 11,067 |
| | Axle-loading, Loaded Front / Rear | lb | 13,910 / 1,932 | 15,807 / 2,099 | 16,524 / 2,262 | 17,489 / 2,506 | 12,814 / 1,798 | 15,018 / 1,808 | 15,642 / 2,039 | 16,616 / 2,167 |
| | Axle-loading, Unloaded Front / Rear | lb | 5,024 / 5,317 | 5,317 / 5,991 | 5,335 / 6,411 | 5,247 / 7,044 | 3,979 / 5,633 | 4,445 / 5,769 | 4,365 / 6,261 | 4,222 / 6,845 |
| Wheels, Chassis, Tire Type | | | Pneumatic, Superelastic | Pneumatic, Superelastic | Pneumatic, Superelastic | Pneumatic, Superelastic | Solid Pneumatic | Solid Pneumatic | Solid Pneumatic | Solid Pneumatic |
| Dimensions | Overhead Guard Height | in | 85.6 | 85.6 | 85.6 | 85.6 | 89.6 | 89.6 | 89.6 | 89.6 |
| | Length to Face of Forks | in | 92.5 | 95 | 97 | 99 | 90.3 | 97.8 | 98.5 | 102 |
| | Overall Width | in | 48 | 48 | 48 | 48 | 47.2 | 47.2 | 47.2 | 49.2 |
| | Turning Radius | in | 82 | 84.4 | 86 | 88 | 76.3 | 84.6 | 85.2 | 86.8 |
| Right-angle Stacking Aisle Width 40" x 48" | | in | 147 | 150 | 152 | 153 | 143.2 | 150.7 | 151.3 | 153.4 |
| Right-angle Stacking Aisle Width 48" x 32" | | in | 155 | 158 | 160 | 161 | 149.7 | 157.8 | 158.4 | 160.5 |
| Performance | Travel Speed Loaded / Unloaded | mph | 10 / 11 | 10 / 11 | 10 / 11 | 10 / 11 | 10.6 / 11.2 | 10.6 / 11.2 | 10.6 / 11.2 | 10.6 / 11.2 |
| | Drive Motor Rating | hp | 18.8 | 18.8 | 18.8 | 18.8 | 12.6 | 12.6 | 12.6 | 12.6 |
| | Pump (Lift) Motor Rating | hp | 20.1 | 20.1 | 20.1 | 20.1 | 30.6 | 30.6 | 30.6 | 30.6 |
| | Battery Voltage | v | 48 | 48 | 48 | 48 | 36 / 48 | 36 / 48 | 36 / 48 | 36 / 48 |
| | Battery Compartment (L x W x H)* | in | 38.7 x 18.3 x 30.1 | 38.7 x 21.1 x 30.1 | 38.7 x 21.1 x 30.1 | 38.7 x 21.1 x 30.1 | 40.7 x 31.5 x 21.2 | 40.7 x 39.4 x 21.2 | 40.7 x 39.4 x 21.2 | 40.7 x 39.4 x 21.2 |
| Others | Type of Drive Control | | AC | AC | AC | AC | AC | AC | AC | AC |

* In this case the Length = the dimension from the left side of the rear counterweight to the right.
The Width = the dimension from the rear of the truck to the forks.

| | | | 25BH-9 | 30BH-9 | 35BH-9 | 40B-9 | 45B-9 | 50B-9 |
|--|-------------------------------------|-----|--------------------|------------------|------------------|--------------------|--------------------|--------------------|
| Identification | Load Capacity | lb | 5,000 | 6,000 | 7,000 | 8,000 | 9,000 | 10,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 10,384 | 11,310 | 12,331 | 15,113 | 16,193 | 17,207 |
| | Axle-loading, Loaded Front / Rear | lb | 13,977 / 1,918 | 15,955 / 1,969 | 17,756 / 2,317 | 21,050 / 2,881 | 23,052 / 3,062 | 24,983 / 3,225 |
| | Axle-loading, Unloaded Front / Rear | lb | 5,115 / 5,269 | 5,655 / 5,655 | 5,686 / 6,671 | 7,725 / 7,388 | 8,060 / 8,133 | 8,331 / 8,876 |
| Wheels, Chassis, Tire Type | | | Solid Pneumatic | Solid Pneumatic | Solid Pneumatic | Solid Pneumatic | Solid Pneumatic | Solid Pneumatic |
| Dimensions | Overhead Guard Height | in | 88.1 | 88.1 | 87 | 93.1 | 93.1 | 91.3 |
| | Length to Face of Forks | in | 93.1 | 98.2 | 102.4 | 117.9 | 117.9 | 119.7 |
| | Overall Width | in | 47.2 | 47.2 | 49.2 | 54.17 | 54.17 | 56.1 |
| | Turning Radius | in | 78.7 | 83.7 | 87.9 | 105.1 | 105.1 | 106.5 |
| Right-angle Stacking Aisle Width 40" x 48" | | in | 145 | 149.5 | 154.2 | 173.4 | 173.4 | 175.0 |
| Right-angle Stacking Aisle Width 48" x 32" | | in | 152 | 156.9 | 161.5 | 181.3 | 181.3 | 182.9 |
| Performance | Travel Speed Loaded / Unloaded | mph | 11.2 / 11.8 | 11.2 / 11.8 | 11.2 / 11.8 | 11.2 / 11.2 | 11.2 / 11.2 | 11.2 / 11.2 |
| | Drive Motor Rating | hp | 14.3 x 2 | 14.3 x 2 | 14.3 x 2 | 18 x 2 | 18 x 2 | 18 x 2 |
| | Pump (Lift) Motor Rating | hp | 35.4 | 35.4 | 35.4 | 50.2 | 50.2 | 50.2 |
| | Battery Voltage | v | 80 | 80 | 80 | 80 | 80 | 80 |
| | Battery Compartment (L x W x H)* | in | 40.5 x 28.1 x 31.2 | 40.5 x 33 x 31.2 | 40.5 x 33 x 31.2 | 40.7 x 39.5 x 30.9 | 40.7 x 39.5 x 30.9 | 40.7 x 39.5 x 30.9 |
| Others | Type of Drive Control | | AC | AC | AC | AC | AC | AC |

* In this case the Length = the dimension from the left side of the rear counterweight to the right.
The Width = the dimension from the rear of the truck to the forks.

13BOP-9



Order Picker

3,000 lbs. capacity · Polyurethane Tire
2,200 lbs capacity Auxiliary Lift option available

15/18/20/23BRP-9



Pantograph Reach Truck

3,000 - 4,500 lbs. capacity · Polyurethane Tire

15/18/20/25BR-X



Moving Mast Reach Truck

3,000-5,000 lbs. capacity · Polyurethane Tire

16/20BRJ-9



Moving Mast Reach Truck

3,200-4,000 lbs. capacity · Polyurethane Tire

| | | 13BOP-9 | | 15BRP-9 | 18BRP-9 | 20BRP-9 | 23BRP-9 |
|-----------------|--|---------|-----------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|
| Identification | Load Capacity | lb | 3,000 | 3,000 | 3,500 | 4,000 | 4,500 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 |
| | Operator Type | | Standing | Standing | Standing | Standing | Standing |
| Weights | Service Weight | lb | 6,470 | 8,781 | 7,408 | 7,727 | 8,600 |
| | Axle-loading, Reach-in, Unloaded Front/Rear | lb | 1,634 / 7,701 | 3,512 / 5,269 | 2,879 / 4,528 | 6,044 / 4,683 | 3,406 / 5,194 |
| | Axle-loading, Reach-out, Unloaded Front/Rear | lb | 3,448 / 3,020 | 7,143 / 4,638 | 7,030 / 3,878 | 7,762.5 / 3,964 | 8,576 / 4,524 |
| Wheels, Chassis | Tire Type (load / drive / caster) | | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber |
| | Service Brake | | Electromagnetic Brake | Electromagnetic Brake | Electromagnetic Brake | Electromagnetic Brake | Electromagnetic Brake |
| Dimensions | Overhead Guard Height | in | 89 | 94.5 | 94.5 | 94.5 | 94.5 |
| | Reach Stroke | in | N/A | 42.8 | 23.3 | 23.3 | 23.3 |
| | Outrigger Inner Dimension | in | 40.2 / 49.2 | 34-50 | 34-50 | 34-50 | 34-50 |
| | Overall Length | in | 117.3 | 104.3** | 93.2** | 95.2** | 97** |
| Performance | Turning Radius (in standard battery compartment) | in | 71.6 | 74.5 | 66.5 | 68.5 | 72.9 |
| | Travel Speed Loaded / Unloaded | mph | 7.5 / 7.5 | 7.3 / 7.3 | 7.3 / 7.3 | 7.3 / 7.3 | 7.3 / 7.3 |
| Performance | Drive Motor Rating | hp | 7.8 | 12.2 | 12.2 | 12.2 | 12.2 |
| | Pump (lift) Motor Rating | hp | 16.4 | 28.7 | 28.7 | 28.7 | 28.7 |
| | Maximum Battery Voltage | v | 24 / 36 | 36 | 36 | 36 | 36 |
| | Battery Compartment (L x W x H)* | | 38.3 x 16.5 x 32.4 | Additional Compartment Widths*** | Additional Compartment Widths*** | Additional Compartment Widths*** | Additional Compartment Widths*** |
| Others | Type of Drive Control | | AC | AC | AC | AC | AC |

* In this case the Length = the dimension from the left side of the rear counterweight to the right. The Width = the dimension from the rear of the truck to the forks.

** Varies dependent upon battery compartment size

*** Available in 14.3" - 20.7". Varies by Battery Type.

| | | 15BR-X | | 18BR-X | 20BR-X | 25BR-X | 16BRJ-9 | 20BRJ-9 |
|-----------------|--|--------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|--|--|
| Identification | Load Capacity | lb | 3,000 | 3,500 | 4,000 | 5,000 | 3,200 | 4,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 |
| | Operator Type | | Standing | Standing | Standing | Standing | Seated | Seated |
| Weights | Service Weight | lb | 5,051 | 5,093 | 6,137 | 6,389 | 7,185 | 8,375 |
| | Axle-loading, Reach-in, Unloaded Front/Rear | lb | 1,790 / 3,260 | 1,649 / 3,444 | 2,167 / 3,971 | 1,997 / 4,392 | 4,442 / 2,743 | 4,954 / 3,422 |
| | Axle-loading, Reach-out, Unloaded Front/Rear | lb | 7,308 / 1,049 | 8,027 / 1,034 | 9,385 / 1,161 | 10,666 / 1,235 | 1,345 / 9,367 | 1,391 / 11,393 |
| Wheels, Chassis | Axle-loading, Reach-in, Loaded Front/Rear | lb | 5,573 / 2,787 | 5,635 / 3,425 | 6,826 / 3,721 | 7,145 / 4,755 | 3,871 / 6,841 | 4,200 / 8,587 |
| | Tire Type (load / drive / caster) | | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber | Polyurethane / Solid Rubber |
| Dimensions | Service Brake | | Disc | Disc | Disc | Disc | Electric | Electric |
| | Overhead Guard Height | in | 89.6 | 89.6 | 90.3 | 90.3 | 83.3 | 84.1 |
| | Reach Stroke | in | 19 | 26 | 24 | 32 | 22.1 | 21.8 |
| | Outrigger Inner Dimension | in | 30.4 / 42.1 | 30.4 / 42.1 | 30.8 / 46.9 | 30.8 / 46.9 | 50.4 / 50 | 50.8 / 50 |
| Performance | Turning Radius (in standard battery compartment) | in | 62.8 | 69.9 | 70.5 | 78.0 | 66.3 | 68.6 |
| | Travel Speed loaded / unloaded | mph | 6.2 / 6.2 | 6.2 / 6.2 | 6.6 / 6.5 | 6.5 / 6.5 | 8.7 / 8.7 | 8.7 / 8.7 |
| Performance | Drive Motor Rating | hp | 8 | 8 | 8 | 8 | 10 | 10 |
| | Pump (lift) Motor Rating | hp | 16 | 16 | 18.7 | 18.7 | 18.7 | 18.7 |
| | Maximum Battery Voltage | v | 48 | 48 | 48 | 48 | 48 | 48 |
| | Battery Compartment (L x W x H)* | | 39.1 x 14.9 x 22.9 | 39.1 x 14.9 x 22.9 | 39.1 x 14.9 x 22.9 | 39.1 x 14.9 x 22.9 | Std: 48.6 x 11.3 x 31.6 Opt: 48.6 x 14.1 x 31.6 | Std: 48.6 x 14.1 x 31.6 Opt: 48.6 x 17 x 31.6 |
| Others | Type of Drive Control | | AC | AC | AC | AC | AC | AC |

* In this case the Length = the dimension from the left side of the rear counterweight to the right. The Width = the dimension from the rear of the truck to the forks.

LPG FORKLIFTS THAT DELIVER MORE

More features. More performance. More durability. Hyundai LPG forklifts deliver all of this with lower emissions and outstanding fuel efficiency. Our lineup includes cushion and pneumatic tire models with capacities from 3,000 to 15,500 lbs.

Designed to handle the toughest jobs, Hyundai LPG forklifts offer you advanced features including our multifunction digital cluster with real-time data, wet disc brakes, and power steering, that reduce your costs as they drive up your profitability.

With their powerful engines, outstanding maneuverability and gradeability, Hyundai forklifts are built to handle a wide range of applications including warehousing, manufacturing, precast concrete, lumber, freight handling and more.

Hyundai forklifts provide operators with greater comfort thanks to full suspension seats, ergonomic pedal designs, adjustable steering wheels, roomy cabs, and controls that minimize fatigue and maximize productivity. Hyundai puts safety first with a comprehensive package that includes features like an auto parking brake and load weight indicator.



LPG FORKLIFTS

15/18LC-7M



LPG Forklift
3,000 - 3,500 lbs. capacity · Cushion Tire

25/30/33LC-9



LPG Forklift
5,000 - 6,500 lbs. capacity · Cushion Tire

| | | | 15LC-7M | 18LC-7M | 25LC-9 | 30LC-9 | 33LC-9 |
|-----------------|--------------------------------------|-------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Identification | Load Capacity | lb | 3,000 | 3,500 | 5,000 | 6,000 | 6,500 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 6,235 | 6,673 | 8,694 | 9,556 | 10,098 |
| | Axle-loading, Loaded Front / Rear | lb | 8,093 / 1,448 | 8,913 / 1,618 | 12,151 / 1,547 | 13,666 / 1,889 | 14,715 / 1,887 |
| | Axle-loading, Unloaded Front / Rear | lb | 2,425 / 3,809 | 2,284 / 4,389 | 3,570 / 5,124 | 3,376 / 6,180 | 3,563 / 6,536 |
| Wheels, Chassis | Tire Size, Front | | 18 x 6 x 12 | 18 x 6 x 12 | 21 x 7 x 15 | 21 x 8 x 15 | 21 x 8 x 15 |
| | Tire Size, Rear | | 14 x 5 x 10 | 14 x 5 x 10 | 16 x 6 x 10.5 | 16 x 6 x 10.5 | 16 x 6 x 10.5 |
| Dimensions | Overhead Guard Height | in | 84.4 | 84.4 | 81.3 | 81.3 | 81.3 |
| | Length to Face of Forks | in | 82.4 | 83.7 | 89.8 | 92.2 | 93.9 |
| | Overall Width | in | 38.6 | 38.6 | 42.1 | 43.7 | 43.7 |
| | Ground Clearance, Loaded, Under Mast | in | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 |
| | Turning Radius | in | 74.5 | 75.6 | 80 | 82 | 82.7 |
| Performance | Travel Speed Unloaded | mph | 10.5 | 10.5 | 9.7 | 9.6 | 9.6 |
| | Engine Manufacturer / Model | | MMC / 2.0L | MMC / 2.0L | Hyundai / L4KB | Hyundai / L4KB | Hyundai / L4KB |
| | Engine Power | hp | 48 @ 2,300 rpm | 48 @ 2,300 rpm | 60 @ 2,300 rpm | 60 @ 2,300 rpm | 60 @ 2,300 rpm |
| | Engine Torque | lb-ft | 110 @ 1,600 rpm | 110 @ 1,600 rpm | 137 @ 1,800 rpm | 137 @ 1,800 rpm | 137 @ 1,800 rpm |
| | No. Cylinder / Cubic Capacity | / cc | 4 / 1,997 | 4 / 1,997 | 4 / 2,359 | 4 / 2,359 | 4 / 2,359 |
| | Service Brake | | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |

15/18/20L-7M



LPG Forklift
3,000 - 4,000 lbs. capacity · Pneumatic Tire

25L/30L-9A,
35LN-9A



LPG Forklift
5,000 - 7,000 lbs. capacity · Pneumatic Tire

35/40/45/50L-9



LPG Forklift
8,000-11,000 lbs. capacity · Pneumatic Tire

70L-7A



LPG Forklift
15,500 lbs. capacity · Pneumatic Tire

| | | | 15L-7M | 18L-7M | 20L-7M | 25L-9A | 30L-9A | 35LN-9A |
|-----------------|--------------------------------------|-------|-----------------|-----------------|-----------------|-----------------|------------------|------------------|
| Identification | Load Capacity | lb | 3,000 | 3,500 | 4,000 | 5,000 | 6,000 | 7,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 5,932 | 6,307 | 6,715 | 8,203 | 9,074 | 9,998 |
| | Axle-loading, Loaded Front / Rear | lb | 8,024 / 1,212 | 8,832 / 1,334 | 9,656 / 1,455 | 12,106 / 1,612 | 13,885 / 1,803 | 15,305 / 2,409 |
| | Axle-loading, Unloaded Front / Rear | lb | 2,623 / 3,307 | 2,528 / 3,778 | 2,438 / 4,275 | 3,306 / 4,844 | 3,505 / 5,569 | 3,195 / 6,802 |
| Wheels, Chassis | Tire Size, Front | | 6.5 x 10 x 12PR | 6.5 x 10 x 12PR | 6.5 x 10 x 12PR | 7 x 12 x 12PR | 8.15 x 15 x 14PR | 8.15 x 15 x 14PR |
| | Tire Size, Rear | | 5 x 8 x 10PR | 5 x 8 x 10PR | 5 x 8 x 10PR | 6.5 x 10 x 12PR | 6.5 x 10 x 12PR | 6.5 x 10 x 12PR |
| Dimensions | Overhead Guard Height | in | 83.1 | 83.1 | 83.1 | 95.4 | 86.2 | 86.2 |
| | Length to Face of Forks | in | 88 | 89.2 | 90.9 | 102.6 | 105 | 109 |
| | Overall Width | in | 42.1 | 42.1 | 42.1 | 47.2 | 48.4 | 48.4 |
| | Ground Clearance, Loaded, Under Mast | in | 4.7 | 4.7 | 4.7 | 5.1 | 5.7 | 5.7 |
| | Turning Radius | in | 78.7 | 79.8 | 81.1 | 92.2 | 95 | 98 |
| Performance | Travel Speed Unloaded | mph | 12.5 | 12.5 | 12.5 | 11 | 11.6 | 11.6 |
| | Engine Manufacturer / Model | | Hyundai / L4KB | Hyundai / L4KB | Hyundai / L4KB | Hyundai / L4KB | Hyundai / L4KB | Hyundai / L4KB |
| | Engine Power | hp | 49 @ 2,450 rpm | 49 @ 2,450 rpm | 49 @ 2,450 rpm | 60 @ 2,300 rpm | 60 @ 2,300 rpm | 60 @ 2,300 rpm |
| | Engine Torque | lb-ft | 118 @ 1,600 rpm | 118 @ 1,600 rpm | 118 @ 1,600 rpm | 137 @ 1,800 rpm | 137 @ 1,800 rpm | 137 @ 1,800 rpm |
| | No. Cylinder / Cubic Capacity | / cc | 4 / 2,359 | 4 / 2,359 | 4 / 2,359 | 4 / 2,359 | 4 / 2,359 | 4 / 2,359 |
| | Service Brake | | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |

| | | | 35L-9 | 40L-9 | 45L-9 | 50L-9 | 70L-7A |
|-----------------|--------------------------------------|-------|------------------|------------------|------------------|------------------|-----------------|
| Identification | Load Capacity | lb | 8,000 | 9,000 | 10,000 | 11,000 | 15,500 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 12,798 | 13,995 | 14,749 | 15,659 | 20,790 |
| | Axle-loading, Loaded Front / Rear | lb | 17,979 / 2,526 | 19,978 / 2,835 | 21,817 / 2,851 | 23,686 / 2,930 | 32,108 / 4,114 |
| | Axle-loading, Unloaded Front / Rear | lb | 5,787 / 7,002 | 6,045 / 7,950 | 6,418 / 8,331 | 6,490 / 9,169 | 8,525 / 12,267 |
| Wheels, Chassis | Tire Size, Front | | 8.25 x 15 x 14PR | 7.5 x 16 x 12PR | 7.5 x 16 x 12PR | 7.5 x 16 x 12PR | 8.25 x 15 |
| | Tire Size, Rear | | 7 x 12 x 14PR | 7 x 12 x 14PR | 7 x 12 x 14PR | 7 x 12 x 14PR | 8.25 x 15 |
| Dimensions | Overhead Guard Height | in | 87 | 87 | 87 | 89 | 100 |
| | Length to Face of Forks | in | 122.4 | 124.6 | 129.3 | 131.8 | 144.9 |
| | Overall Width | in | 54 | 68.5 | 68.5 | 68.5 | 82.2 |
| | Ground Clearance, Loaded, Under Mast | in | 6.7 | 6.1 | 6.1 | 6.1 | 7.7 |
| | Turning Radius | in | 112.9 | 114.8 | 118.5 | 120.2 | 132.7 |
| Performance | Travel Speed Unloaded | mph | 19.7 | 18.6 | 18.5 | 18.5 | 14 |
| | Engine Manufacturer / Model | | Kubota / WG3800 | Kubota / WG3800 | Kubota / WG3800 | Kubota / WG3800 | PSI / 4.3 |
| | Engine Power | hp | 87.2 @ 2,450 rpm | 87.2 @ 2,450 rpm | 87.2 @ 2,450 rpm | 87.2 @ 2,450 rpm | 106 @ 2,300 rpm |
| | Engine Torque | lb-ft | 214 @ 1,200 rpm | 214 @ 1,200 rpm | 214 @ 1,200 rpm | 214 @ 1,200 rpm | 246 @ 1,400 rpm |
| | No. Cylinder / Cubic Capacity | / cc | 4 / 2,969 | 4 / 3,769 | 4 / 3,769 | 4 / 3,769 | 6 / 4,294 |
| | Service Brake | | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |

DIESEL FORKLIFTS THAT DELIVER MORE

More power. More strength. More capability. Hyundai diesel forklifts are the workhorses you need to tackle the toughest outdoor jobs on any terrain. Our lineup includes models with capacities ranging from 5,000 to 55,000 lbs.

Hyundai diesel forklifts feature powerhouse engines that deliver loads of torque with low emissions and rugged transmissions for outstanding responsiveness. Add in heavy-duty drive axles and virtually maintenance-free wet disc brakes, and you have machines that offer more than just brute strength.

Built to withstand years of punishment, Hyundai diesel forklifts also feature cabs that minimize fatigue and maximize productivity. Inside are our multifunction display with real-time data, full suspension seats, efficient climate control systems, power steering, and ergonomically placed controls.

So, whether it's working at construction sites, ports, lumber mills, mines, or handling precast concrete, building materials, or containers, nothing does the job better, quicker, or more efficiently than Hyundai diesel forklifts.



> DIESEL FORKLIFTS

25/30D-9V
35DN-9V



Diesel Forklift
5,000 - 7,000 lbs. capacity

35/40/45D-9F
50DA-9F



Diesel Forklift
8,000 - 11,000 lbs. capacity

| | | | 25D-9V | 30D-9V | 35DN-9V | 35D-9F | 40D-9F | 45D-9F | 50DA-9F |
|-----------------|---|----------|-------------------|-------------------|-------------------|------------------|------------------|------------------|------------------|
| Identification | Load Capacity | lb | 5,000 | 6,000 | 7,000 | 8,000 | 9,000 | 10,000 | 11,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 8,583 | 9,484 | 10,267 | 12,994 | 14,193 | 15,199 | 16,089 |
| | Axle-loading, Loaded Front / Rear | lb | 12,229 / 1,867 | 14,019 / 2,077 | 15,655 / 2,328 | 18,082 / 2,628 | 20,082 / 2,930 | 21,757 / 3,362 | 23,558 / 3,554 |
| | Axle-loading, Unloaded Front / Rear | lb | 3,483 / 5,102 | 3,640 / 5,845 | 3,545 / 6,722 | 5,891 / 7,103 | 6,148 / 8,046 | 6,082 / 9,116 | 6,142 / 9,947 |
| Wheels, Chassis | Tire Size, Front | | 7 x 12 x 12PR | 8.15 x 15 x 14PR | 8.15 x 15 x 14PR | 8.25 x 15 x 14PR | 7.5 x 16 x 12PR | 7.5 x 16 x 12PR | 7.5 x 16 x 12PR |
| | Tire Size, Rear | | 6.5 x 10 x 12PR | 6.5 x 10 x 12PR | 6.5 x 10 x 12PR | 7 x 12 x 14PR | 7 x 12 x 14 R | 7 x 12 x 14PR | 7 x 12 x 14PR |
| Dimensions | Overhead Guard Height | in | 85.8 | 86.4 | 86.4 | 93 | 95.5 | 95.5 | 95.5 |
| | Length to Face of Forks | in | 103.1 | 108.3 | 108.3 | 122.5 | 124.7 | 127.4 | 130 |
| | Overall Width Single Drive Tire (Dual Drive Tire Option) | in | 47.2 | 48.4 | 48.4 | 53.9 (68.7) | 53.9 (68.7) | 53.9 (68.7) | 53.9 (68.7) |
| | Ground Clearance, Loaded, Under Mast | in | 5.1 | 5.7 | 5.7 | 6.7 | 6.1 | 6.1 | 6.1 |
| | Turning Radius | in | 92.6 | 97.7 | 97.7 | 113 | 114.8 | 116.7 | 118.5 |
| Performance | Travel Speed Unloaded | mph | 10.7 | 11.4 | 11.4 | 16.5 | 16 | 15.9 | 15.9 |
| | Engine Manufacturer / Model | | HDI DM02 | HDI DM02 | HDI DM02 | Kubota / V3800 | Kubota / V3800 | Kubota / V3800 | Kubota / V3800 |
| | Engine Power | hp | 67.7 @ 2,300 rpm | 67.7 @ 2,300 rpm | 67.7 @ 2,300 rpm | 74.3 @ 2,200 rpm | 74.3 @ 2,200 rpm | 74.3 @ 2,200 rpm | 74.3 @ 2,200 rpm |
| | Engine Torque | lb-ft | 180.7 @ 1,600 rpm | 180.7 @ 1,600 rpm | 180.7 @ 1,600 rpm | 228 @ 1,500 rpm | 228 @ 1,500 rpm | 228 @ 1,500 rpm | 228 @ 1,500 rpm |
| | No. Cylinder / Cubic Capacity | / cc | 4 / 2,392 | 4 / 2,199 | 4 / 2,199 | 4 / 3,769 | 4 / 3,769 | 4 / 3,769 | 4 / 3,769 |
| | Service Brake | | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |
| | Fuel Consumption Rate / VDI | gal / hr | .71 | .8 | .85 | 1.27 | 1.27 | 1.27 | 1.27 |

> DIESEL FORKLIFTS

35/40/45D-9



Diesel Forklift
8,000 - 10,000 lbs. capacity

50DA-9



Diesel Forklift
11,000 lbs. capacity

50/70D-9



Diesel Forklift
11,000 - 15,500 lbs. capacity

80D-9



Diesel Forklift
17,500 lbs. capacity

100D-9V



Diesel Forklift
22,000 lbs. capacity

110/130/160D-9



Diesel Forklift
25,000 - 36,000 lbs. capacity

160D-9L / 180D-9B



Diesel Forklift
36,000-40,000 lbs. capacity

250D-9



Diesel Forklift
55,000 lbs. capacity

| | | | 35D-9 | 40D-9 | 45D-9 | 50DA-9 | 50D-9 | 70D-9 |
|-----------------|---|-------|------------------|------------------|------------------|------------------|------------------|------------------|
| Identification | Load Capacity | lb | 8,000 | 9,000 | 10,000 | 11,000 | 11,000 | 15,500 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 24 |
| Weights | Service Weight | lb | 13,082 | 14,295 | 15,212 | 16,131 | 19,599 | 23,091 |
| | Axle-loading, Loaded Front / Rear | lb | 17,948 / 2,851 | 20,078 / 3,034 | 21,806 / 3,327 | 23,541 / 3,611 | 26,792 / 3,730 | 33,347 / 5,011 |
| | Axle-loading, Unloaded Front / Rear | lb | 5,756 / 7,326 | 6,144 / 8,148 | 6,131 / 9,081 | 6,124 / 10,005 | 9,940 / 9,557 | 9,757 / 13,166 |
| Wheels, Chassis | Tire Size, Front | | 8.25 x 15 x 14PR | 7.5 x 16 x 12PR | 7.5 x 16 x 12PR | 7.5 x 16 x 12PR | 8.25 x 15 x 14PR | 8.25 x 15 x 14PR |
| | Tire Size, Rear | | 7 x 12 x 14PR | 7 x 12 x 14PR | 7 x 12 x 14PR | 7 x 12 x 14PR | 8.25 x 15 x 14PR | 8.25 x 15 x 14PR |
| Dimensions | Overhead Guard Height | in | 92.91 | 92.52 | 95.52 | 95.52 | 106 | 106 |
| | Length to Face of Forks | in | 127 | 127 | 129 | 130 | 139.6 | 144.3 |
| | Overall Width Single Drive Tire (Dual Drive Tire Option) | in | 54 (68.5) | 54 (68.5) | 54 (68.5) | 54 (68.5) | 82.2 | 82.2 |
| | Ground Clearance, Loaded, Under Mast | in | 6.7 | 6.1 | 6.1 | 6.1 | 7.7 | 7.7 |
| | Turning Radius | in | 116 | 116 | 118 | 118.5 | 130.5 | 135.3 |
| Performance | Travel Speed Unloaded | mph | 16.5 | 16 | 15.9 | 15.9 | 21.1 | 20.9 |
| | Engine Manufacturer / Model | | Cummins / QSF3.8 | Cummins / QSF3.8 | Cummins / QSF3.8 | Cummins / QSF3.8 | Cummins / QSF3.8 | Cummins / QSF3.8 |
| | Engine Power | hp | 101 @ 2,200 rpm | 101 @ 2,200 rpm | 101 @ 2,200 rpm | 101 @ 2,200 rpm | 101 @ 2,200 rpm | 101 @ 2,200 rpm |
| | Engine Torque | ft-lb | 306 @ 1,600 rpm | 306 @ 1,600 rpm | 306 @ 1,600 rpm | 306 @ 1,600 rpm | 306 @ 1,600 rpm | 306 @ 1,600 rpm |
| | No. Cylinder / Cubic Capacity | / cc | 4 / 3,726 | 4 / 3,726 | 4 / 3,726 | 4 / 3,726 | 4 / 3,726 | 4 / 3,726 |
| | Service Brake | | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |
| | Fuel Consumption Rate | g/h | 1.4 | 1.4 | 1.4 | 1.4 | 1.3 | 1.3 |

| | | | 80D-9 | 100D-9V | 110D-9 | 130D-9 | 160D-9 | 160D-9L | 180D-9B | 250D-9 |
|-----------------|--------------------------------------|-------|------------------|-----------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Identification | Load Capacity | lb | 17,500 | 22,000 | 25,000 | 29,000 | 36,000 | 36,000 | 40,000 | 55,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 48 | 36 | 48 |
| Weights | Service Weight | lb | 25,794 | 28,823 | 36,048 | 37,459 | 43,746 | 52,810 | 52,810 | 85,533 |
| | Axle-loading, Loaded Front / Rear | lb | 38,047 / 5,384 | 45,056 / 5,814 | 53,447 / 6,852 | 59,734 / 6,552 | 70,568 / 8,453 | 82,559 / 5,525 | 86,379 / 6,113 | 128,556 / 12,092 |
| | Axle-loading, Unloaded Front / Rear | lb | 11,310 / 14,484 | 12,427 / 16,396 | 17,946 / 18,102 | 17,778 / 19,848 | 20,825 / 22,919 | 26,599 / 26,209 | 26,599 / 26,209 | 43,003 / 42,529 |
| Wheels, Chassis | Tire Size, Front | | 9 x 20 x 14PR | 9 x 20 x 14PR | 10 x 20 x 16PR | 10 x 20 x 16PR | 12 x 20 x 18PR | 12 x 20 x 20PR | 12 x 20 x 20PR | 14 x 24 x 32PR |
| | Tire Size, Rear | | 9 x 20 x 14PR | 9 x 20 x 14PR | 10 x 20 x 16PR | 10 x 20 x 16PR | 12 x 20 x 18PR | 12 x 20 x 20PR | 12 x 20 x 20PR | 14 x 24 x 32PR |
| Dimensions | Overhead Guard Height | in | 103 | 105.5 | 116 | 116 | 117.3 | 121 | 121 | 130 |
| | Length to Face of Forks | in | 156.3 | 167.9 | 179.9 | 180.3 | 200 | 219 | 219 | 250 |
| | Overall Width | in | 86.4 | 89.2 | 96.5 | 96.5 | 98.3 | 100 | 100 | 120.9 |
| | Ground Clearance, Loaded, Under Mast | in | 9.8 | 9.8 | 9.8 | 9.8 | 9.8 | 9.6 | 9.6 | 11.8 |
| | Turning Radius | in | 145.7 | 156.1 | 171.3 | 171.3 | 192.7 | 208.8 | 205.5 | 228.6 |
| Performance | Travel Speed Unloaded | mph | 21.8 | 20.3 | 22.1 | 21.9 | 21.9 | 21.5 | 21.8 | 18.8 |
| | Engine Manufacturer / Model | | Cummins / QSF3.8 | Cummins / F3.8 | Cummins / QSB6.7 | Cummins / QSB6.7 | Cummins / QSB6.7 | Cummins / QSB6.7 | Cummins / QSB6.7 | Cummins / QSL9 |
| | Engine Power | hp | 101 @ 2,200 rpm | 120 @ 2,200 rpm | 164 @ 2,300 rpm | 164 @ 2,300 rpm | 164 @ 2,300 rpm | 164 @ 2,300 rpm | 164 @ 2,300 rpm | 274 @ 2,200 rpm |
| | Engine Torque | ft-lb | 306 @ 1,600 rpm | 371 @ 1,500 rpm | 539 @ 1,500 rpm | 539 @ 1,500 rpm | 539 @ 1,500 rpm | 539 @ 1,500 rpm | 539 @ 1,500 rpm | 897 @ 1,500 rpm |
| | No. Cylinder / Cubic Capacity | / cc | 4 / 3,726 | 4 / 3,726 | 6 / 6,690 | 6 / 6,690 | 6 / 6,690 | 6 / 6,690 | 6 / 6,690 | 6 / 8,849 |
| | Service Brake | | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |
| | Fuel Consumption Rate | g/h | 1.35 | 1.3 | 3.19 | 3.19 | 3.2 | 3.2 | 3.2 | 6.8 |

PALLET JACKS, TUGGERS, STACKERS THAT DELIVER MORE

More energy efficiency. More features. More convenience. Hyundai Class III forklifts are designed to increase your productivity as you store, transport, or pick items throughout your facilities. Hyundai offers electric and manual pallet jacks, tuggers, stackers, and walkie-riders in a wide array of capacities.

Across our line, you'll find features like maintenance-free AC drive motors, reliable, high performance controllers, robust German-built tillers, heavy-duty construction, and easy access maintenance points.

Highly efficient machines, Hyundai electric pallet jacks, tuggers and stackers also include Li-ion power to bring you lower energy costs, less maintenance, opportunity charging, and extended working time.

To keep your operation moving smoothly, our equipment includes advanced features like CAN-bus technology to reduce downtime; tillers, handles and controls designed to minimize operator fatigue and maximize handling precision; and fast travel speeds to move more pallets more quickly shift after shift.



CLASS III PALLET JACKS

33/45PWN



Electric Pallet Jack
3,300 - 4,500 lbs. capacity

40/45PPW



Electric Pallet Jack
4,000 - 4,500 lbs. capacity

60/80PPR



Walkie/Rider
6,000 - 8,000 lbs. capacity

| | | 33PWN | 45PWN | 40PPW | 45PPW | 60PPR | 80PPR | |
|-----------------|-------------------------------------|-------|---------------------|---------------------|----------------------------|------------------------------|--|------------------------------|
| Identification | Load Capacity | lb | 3,300 | 4,500 | 4,000 | 4,500 | 6,000 | 8,000 |
| | Load Center | in | 24 | 24 | 24 | 24 | 24 | 48 |
| Weights | Service Weight | lb | 278 | 337 | 913 | 1,177 | 2,330 | 2,465 |
| | Axle-loading, Loaded Front / Rear | lb | 1,102 / 2,469 | 1,369 / 3,368 | 1,727 / 3,146 | 1,881 / 3,696 | 3,100 / 5,280 | 2,860 / 7,524 |
| | Axle-loading, Unloaded Front / Rear | lb | 211 / 60 | 254 / 75 | 735 / 176 | 913 / 264 | 1,870 / 550 | 2,024 / 440 |
| Wheels, Chassis | Tire Type | | Polyurethane | Polyurethane | Polyurethane | Polyurethane | Polyurethane | Polyurethane |
| Dimensions | Length to Face of Forks | in | 15 | 15.2 | 23.4 | 23.4 | 43 | 43 |
| | Overall Width | in | 21.3 | 21.3 | 28.7 | 28.7 | 37 / 37.8 | 37 / 37.8 |
| | Fork Length | in | 45.3 | 45.3 | 48 | 45.3 | 36, 42, 48, 54, 60, 96 Standard Tip | 84, 93, 96 Extended Tip |
| | Turning Radius | in | 52.4 | 52.6 | 60 | 59 | 84.4 | 104.7 |
| Performance | Travel Speed Loaded / Unloaded | mph | 2.8 / 3.0 | 3.0 / 3.2 | 3.1 / 3.3 | 3.5 / 3.7 | 6.2 / 8.7 | 5.9 / 7.5 |
| | Drive Motor Rating | hp | 0.87 | 1.02 | 1 | 1.7 | 5.1 | 5.1 |
| | Pump (Lift) Motor Rating | hp | 0.67 | 1.08 | 1.1 | 1.1 | 3 | 3 |
| | Battery Voltage | v | 24 | 48 | 24 | 24 | 24 | 24 |
| | Battery Type | | Li-Ion Battery Pack | Li-Ion Battery Pack | AGM or Li-Ion Battery Pack | Industrial or Li-Ion Battery | Industrial or Li-Ion Battery | Industrial or Li-Ion Battery |
| | Battery Compartment (L x W x H) | in | N/A | N/A | N/A | 25 x 8.5 x 26.5 | 32.7 x 12.9 x 23.2 | 32.7 x 12.9 x 23.2 |
| Others | Type of Drive Control | | Brushless DC | Brushless DC | AC | AC | AC | AC |

22PSWD



Walkie Straddle Stacker
2,600 lbs. capacity

35/40PSW



Walkie Straddle Stacker
3,500 - 4,000 lbs. capacity

66/110TT



Tugger
6,600 - 11,000 lbs. capacity

MPW55-2748



Manual Pallet Jack
5,500 lbs. capacity

| | | 22PSWD | | 35PSW | 40PSW | 66TT | 110TT | MPW55-2748 |
|-----------------|-------------------------------------|--------|----------------|----------------------|----------------------|---------------------|--------------------|--------------|
| Identification | Load Capacity | lb | 2,600 | 3,500 | 4,000 | 6,600 | 11,000 | 5,500 |
| | Load Center | in | 24 | 24 | 24 | N/A | N/A | 24 |
| Weights | Service Weight | lb | 1,421-1,675 | 3,263 | 3,439 | 2,094 | 2,294 | 175 |
| | Axle-loading, Loaded Front / Rear | lb | 1,639 / 2,816 | 1,823 / 4,967 | 1,966 / 5,243 | N/A | N/A | N/A |
| | Axle-loading, Unloaded Front / Rear | lb | 1,375 / 440 | 1,905 / 1,358 | 2,037 / 1,402 | 1,212 / 882 | 1,345 / 902 | N/A |
| Wheels, Chassis | Tire Type | | Polyurethane | Polyurethane | Polyurethane | Solid Rubber | Solid Rubber | Polyurethane |
| Dimensions | Overall Length | in | 25.2 | 36.4 | 37 | 56.3 | 56.3 | N/A |
| | Overall Width | in | 31.5 | 32.1 | 32.1 | 31.9 | 31.9 | 20.5 |
| | Fork Length | in | 42 | 42 | 42 | N/A | N/A | 48 |
| | Turning Radius | in | 53 | 61 | 61 | 52.5 | 52.5 | N/A |
| Performance | Travel Speed, Loaded / Unloaded | mph | 2.6 / 2.8 | 3.4 / 3.7 | 3.4 / 3.7 | 3.7 / 5.6 | 4.3 / 7.5 | N/A |
| | Drive Motor Rating | hp | .87 | 1.88 | 1.88 | 2.5 | 3.5 | N/A |
| | Pump (Lift) Motor Rating | hp | 2.95 | 4.29 | 4.29 | N/A | N/A | N/A |
| | Battery Voltage | v | 24 | 24 | 24 | 24 / 375 | 24 / 465 | N/A |
| | Battery Type | | Li-Ion Battery | Li-Ion Battery | Li-Ion Battery | Li-Ion Battery | Li-Ion Battery | N/A |
| Other | Battery Compartment (L x W x H) | in | 13 x 6.75 x 11 | 29.61 x 6.77 x 25.87 | 29.61 x 6.77 x 25.87 | 30.25 x 16.5 x 26.5 | 32.5 x 16.5 x 26.5 | N/A |
| | Type of Drive Control | | DC | AC | AC | AC | AC | N/A |

THE HYUNDAI DEALER NETWORK DELIVERING MORE BEFORE AND AFTER YOU BUY

Choosing the right equipment is essential to keeping your operation running, and running efficiently, economically, and profitably. Your Hyundai Material Handling dealer offers you the expert advice you need to make the right equipment choice.

Hyundai forklifts are sold and supported by a comprehensive dealer network with more than 150 locations across the United States and Canada. They're your professional and reliable connection to Hyundai equipment and the vast global resources we provide.

After your purchase, you can count on your Hyundai Material Handling dealer for servicing by experienced, professional technicians, fast parts delivery backed up by our dedicated parts center, staff training, all the services you need to keep downtime down to a minimum.

When it comes to innovative, high performance equipment and outstanding service and support, no one delivers more than Hyundai Material Handling.





HD HYUNDAI | MATERIAL
XITESOLUTION | HANDLING

6100 Atlantic Blvd.
Norcross, GA 30071

678-823-7777
hyundaimaterialhandling.com